COCHLEAR IMPLANT COMPARISON CHART

DISCLAIMER: FTC provisions (16 CFR Part 255) regulate product endorsements, testimonials, and blogs, specifically in the Revised Endorsement Guides. This chart has been created and maintained by Tom Hannon, a bilateral Advanced Bionics recipient, and Howard Samuels, a bilateral Advanced Bionics recipient and a volunteer Bionic Ear Association (BEA) mentor; both are equally responsible for the concept, format, research, writing and editing, and neither have any compensated relationship with a cochlear implant manufacturer. Information provided in this chart may vary on market location; more current information may be available from the manufacturer. Any errors or omissions are our own; contact us with any corrections. Please feel free to print or distribute this chart; the latest version will always be available at: CochlearImplantHELP.com

| | ADVANCED BIONICS | COCHLEAR | MED-EL | COMMENTS |
|--------------------------------|---|---|--|---|
| | AB | Cochlear™ | MED®EL | |
| | Advanced Bionics | Cochlear ¹ | MED-EL | |
| CORPORATE OWNERSHIP | Owned by: Sonova Holding AG ² Traded as: PHBN: GR SONVF: US SOON1: EB SOON: BQ SOON: TQ SONVY: US | Owned by: Cochlear Limited Traded as: COH: AU CHEOF: US OC5: GR CHEOY: US | Founded & privately owned by: Prof. Erwin Hochmair + Dr. Ingeborg Hochmair | |
| ESTABLISHED, LOCATION | AB: 1993 California, USA Sonova: 1947 Switzerland | 1981 Australia | 1977 Austria | |
| US PATENTS (AS OF 7-OCT-16) | 516 | 476 | 199 | USA patents only to avoid global duplications: US Patent Office Quick Search by "Assignee Name" Google Patent Search |
| ESTIMATED MARKET SHARE | 20% | 55% | 20% | Remaining 5% includes Oticon (Neurelec) & Nurotron. |
| CURRENT IMPLANT | HiRes Ultra ³ HiRes 90K Advantage HiRes 90k | CI532 Slim Modiolar ⁴ CI512 Contour Advance CI522 Slim Straight CI24RE Contour Advance (CA) or Straight (ST) ⁵ CI24R Double Array | SYNCHRONY CONCERT ⁶ SONATA | Latest implant system from each manufacturer may not be available in all markets. |
| MAXIMUM STIMULATION RATE | 83,000 PPS | 32,000 PPS ⁷ | 51,000 PPS | PPS rate is the number of updates per second the implant is capable of providing. |
| CHANNELS | 16 (120 virtual) | 22 | 12 | |

⁻

¹ Cochlear images provided courtesy of Cochlear™ Americas, © 2009 Cochlear Americas

² Sonova Holding AG also owns Phonak.

³ FDA Approved. Pending market release.

⁴ FDA Approved. Pending market release.

⁵ A combined cochlear implant & hearing aid (CI/HA) system uses the same implant electronics as a conventional cochlear implant. Cochlear's L24 implant is the CI24 implant with a shortened electrode array.

⁶ For brevity the MED-EL CONCERT brand name has been shortened to CONCERT.

⁷ CI24R Double Array 14,400 PPS

| | ADVANCED BIONICS | COCHLEAR | MED-EL | COMMENTS |
|--|--|---|--|---|
| ELECTRODES | 16 | 22 | Up to 24 | Electrical contacts between the implant and the cochlea. |
| ELECTRODE DRIVERS | 16 | 1 | 12 | Each electrode driver contains a positive and negative current source. |
| MAXIMUM SIMULTANEOUS ELECTRODE DRIVERS | 4 | 1 | 1 | |
| RF CARRIER & DATA RATE | 49 MHz, 1Mb sec ⁸ | 5 MHz, 0.5Mb sec ⁸ | 12 MHz, 0.6Mb sec 8 | Sound processor communication frequency & data rate. |
| ELECTRODE ARRAY | HiFocus Mid-Scala HiFocus 1J, HiFocus Helix | CI532 Slim Modiolar CI512/CI522 Profile Series CI24RE (CA) ⁹ , CI24RE (ST) ⁹ CI24R Double Array ⁹ | FLEX SOFT, FLEX 28, FLEX 24, FLEX 20 FORM 24, FORM 19 Standard, Medium, Compressed | Multiple array types provide options for unusual physiologies. New MED-EL FLEX Portfolio arrays are smaller in diameter. |
| LENGTH OF ELECTRODE ARRAYS | HiFocus Mid-Scala: 18.5/15.0 1J: 25.0/17.0 Helix: 24.5/13.25 | CI532: Data Pending CI512/CI522: 32.0/19.0 CI24RE (CA): 23.9/15.0 CI24RE (ST): 28.0/16.4 CI24R: 15.0/8.25 | CLASSIC Series Standard: 31.5/26.4 Medium: 24.0/20.9 Compressed: 15.0/12.1 FLEX SERIES FLEX SOFT: 31.5/26.4 FLEX 28: 28.0/23.1 FLEX 24: 24.0/20.9 FLEX 20: 20.0/15.4 FORM Series FORM 24 24.0/18.7 FORM 19 19.0/14.3 | Measurements in millimeters (mm) & are total/active lengths. |
| IMPLANT HOUSING & COIL DIMENSIONS (WITHOUT ARRAY) | HiRes Ultra: 56.2 x 28.5 x 4.5 Advantage: 56.0 x 28.0 x 5.5 HiRes 90K: 56.0 x 28.0 x 5.5 | CI532: 50.5 x 31.0 x 3.9 CI512/CI522: 50.5 x 31.0 x 3.9 CI24RE/CI24R: 51.2 x 30.9 x 6.9 | SYNCHRONY: 45.7 x 25.4 x 4.5 CONCERT: 45.7 x 25.4 x 4.5 SONATA: 45.7 x 24.8 x 5.9 | Length (L) x Width (W) x Depth (D) Measurements in millimeters (mm). |

 ⁸ Zeng FG, Rebscher S, Harrison W, Sun X, Feng H., "Cochlear Implants: System Design, Integration, and Evaluation" Page 63 Table II
 ⁹ Cochlear Cl24RE housing and coil available with two electrode array configurations, Contour Advance (CA) and Full Band Straight (ST). Cl24R is configured with a split array for ossification.

| | ADVANCED BIONICS | COCHLEAR | MED-EL | COMMENTS |
|--|--|---|---|---|
| BONE RECESS DEPTH | HiRes Ultra: N/A ¹⁰ Advantage: 3.0 HiRes 90K: 3.0 | CI532: Data Pending CI512/CI522: 2.2 CI24RE/CI24R: 2.3 | SYNCHRONY: 2.0 Maximum CONCERT: 2.0 Maximum ¹¹ SONATA: 2.0 Maximum | Bone recess measurements in millimeters (mm), according to manufacturer recommendations. Elevation from bone referred to as "bump height." |
| ELEVATION FROM BONE WITH RECESS WELL | HiRes Ultra: N/A Advantage: 2.5 HiRes 90K: 2.5 | CI532: Data Pending CI512/CI522: 1.7 CI24RE/CI24R: 4.6 | SYNCHRONY: 2.5 CONCERT: 2.5 SONATA: 3.9 | See American Academy of Audiology "To Drill or not to Drill a Well for the Cochlear Implant's Internal Device?" |
| ELEVATION FROM BONE WITHOUT RECESS WELL | HiRes Ultra: 4.5 Advantage: 5.5 HiRes 90K: 5.5 | CI532: Data Pending CI512/CI522: 3.9 CI24RE/CI24R: 6.9 | SYNCHRONY: 4.5 CONCERT: 4.5 SONATA: 5.9 | Implant migration may occur if manufacturer's surgical instructions are not followed. Always consult with your implant center regarding implant anchoring questions. |
| IMPLANT WEIGHT | HiRes Ultra: 10.0 Advantage: 12.0 HiRes 90K: 12.0 | CI532: 8.6 CI512/CI522: 8.8 CI24RE/CI24R: 9.5 | SYNCHRONY: 7.6 CONCERT: 7.6 SONATA: 8.6 | Weight in grams (g). |
| IMPLANT CASING | HiRes Ultra: Titanium Advantage: Titanium HiRes 90K: Titanium | CI532: Titanium CI512/CI522: Titanium CI24RE/CI24R: Titanium | SYNCHRONY: Titanium CONCERT: Titanium SONATA: Titanium | |
| IMPACT RESISTANCE | HiRes Ultra: 2.5 Joules Advantage: 6.0 Joules HiRes 90K: 6.0 Joules | CI532: 2.5 Joules CI512/CI522: 2.5 Joules CI24RE/CI24R: 1.0 Joules | SYNCHRONY: 2.5 Joules CONCERT: 2.5 Joules SONATA: 2.5 Joules | Damage resistance from accidental impact. |
| REMOVABLE MAGNET | HiRes Ultra: Yes Advantage: Yes HiRes 90K: Yes | CI532: Yes CI512/CI522: Yes CI24RE/CI24R: Yes | SYNCHRONY: Yes CONCERT: No SONATA: No | MRI magnet safety varies by regulatory approval & may be available with a special compression bandage; Cochlear instructions and white paper in example. |
| MRI WITH MAGNET | HiRes Ultra: Up to 1.5 Tesla Advantage: Up to 1.5 Tesla ¹² HiRes 90K: Up to 1.5 Tesla | CI532: Up to 1.5 Tesla CI512/CI522: Up to 1.5 Tesla ¹³ CI24RE/CI24R: Up to 1.5 Tesla | SYNCHRONY: Up to 3.0 Tesla ¹⁴ CONCERT: Up to 1.5 Tesla SONATA: Up to 1.5 Tesla | All implants undergoing an MRI can produce significant artifact and/or other adverse events, such as magnet dislocation. MRI Safety websites: |
| MRI WITH MAGNET REMOVED | HiRes Ultra: Up to 3.0 Tesla Advantage: Up to 1.5 Tesla HiRes 90K: Up to 1.5 Tesla | CI532: Up to 3.0 Tesla CI512/CI522: Up to 3.0 Tesla ¹⁵ CI24RE/CI24R: Up to 3.0 Tesla | SYNCHRONY: Up to 3.0 Tesla CONCERT: N/A SONATA: N/A | Cochlear Implant Safety Cochlear Implant List MRIs in the immediate vicinity of the implant require magnet removal. Magnet removal should always be coordinated with the implant center & implant manufacturer. |
| WARRANTY | 10 years | 10 years | 10 years | |
| CURRENT RELIABILITY | 2015 Reliability Report | 2015 Reliability Report | 2015 Reliability Information | All manufacturers claim top reliability. Search the FDA database; Product Code: MCM Reliability overview. |

Designed for surface mounting.

11 Available without or with fixation pins requiring two 1.0mm x 1.4mm recesses.

12 MRI with magnet intact not regulatory approved in all global markets. Advanced Bionics & MRI compatibility.

13 MRI with magnet intact not regulatory approved in all global markets. Cochlear's implants are FDA approved with magnet intact up to stated field strength, except the Cl24R. Cochlear & MRI compatibility.

14 MRI with magnet intact not regulatory approved in all global markets. MED-EL implants are FDA approved with magnet intact up to stated field strength. MED-EL & MRI compatibility.

15 MRI with magnet removed not regulatory approved in all global markets. Cochlear's implants are FDA approved with magnet removed up to stated field strength, except the Cl24R.

| | ADVANCED BIONICS | COCHLEAR | MED-EL | COMMENTS |
|--|--|---|--|--|
| CURRENT SOUND PROCESSOR IMAGES NOT TO SCALE | Naída CI Q90 User Guide | Nucleus® 6 ¹⁶ CP910 & CP920 User Guide | SONNET User Manual | Latest sound processor from each manufacturer may not be available in all markets; previous generation sound processor may still be available. User guides/manuals linked within this chart may not be the manufacturer's latest edition. |
| | Neptune User Guide | Kanso CP950 User Guide | RONDO User Manual | Each manufacturer offers multiple wearing options. |
| CURRENT SOUND PROCESSOR IMAGES NOT TO SCALE | · | | | |
| | Naída CI Q90 MyPilot User Guide | Nucleus® 6 System CR230 Remote Assistant User Guide | FineTuner User Instructions (pages 11-14) | Remote control discussion. |
| REMOTE CONTROL IMAGES NOT TO SCALE | To be a second of the second o | CR210 Remote Control User Guide | | |
| PROCESSOR DIMENSIONS AS INDICATED IN MANUFACTURER'S LITERATURE | Naída with PowerCel 110 Mini: 40 x 9 x 19 PowerCel 110: 49 x 9 x 19 PowerCel 170 Mini: 50 x 9 x 19 PowerCel 170: 55 x 9 x 19 PowerCel 230: 59 x 9 x 19 Zinc-Air Pak: 53 x 9 x 19 Neptune: 26 x 18 x 60 Neptune Connect: 17 x 18 x 58 | Nucleus 6 CP910 with Compact: 42.3 x 9 x 47.7 Standard: 51.3 x 9 x 47.7 Zinc-air: 51.3 x 9 x 47.7 Nucleus 6 CP920 with Compact: 39.1 x 9 x 47.7 Standard: 48.1 x 9 x 47.7 Zinc-air: 48.1 x 9 x 47.7 Kanso: 40.9 x 35.2 x 11.4 | SONNET with Zinc-air: 56.7 x 9.3 x 37.4 Standard: 56.7 x 9.3 x 37.4 Micro: 51.4 x 9.3 x 37.4 RONDO: 44.1 x 37.2 x 12.1 | Dimensions in millimeters Height (H) x Width (W) x Depth (D) Naída depth dimensions are without an ear-hook or T-Mic 2. Neptune dimensions with water- proof configuration. Cochlear Nucleus 6 dimensions are with a medium ear-hook. |

¹⁶ If the Nucleus 6 CP910 & Nucleus 6 CP920 features/functions are the same use of Nucleus 6 will refer to both.

| | ADVANCED BIONICS | COCHLEAR | MED-EL | COMMENTS |
|--|--|---|---|--|
| PROCESSOR WEIGHT | Naída with PowerCel 110 Mini: 11.0 PowerCel 110: 11.0 PowerCel 170 Mini: 12.0 PowerCel 170: 13.0 PowerCel 230: 13.0 Zinc-Air Pak: 13.0 Neptune: 32 Neptune with Connect: 43.0 | Nucleus 6 CP910 with Compact: 10.5 Standard: 13.0 Zinc-air: 12.8 Nucleus 6 CP920 with Compact: 9.8 Standard: 12.4 Zinc-air: 12.1 Kanso with Magnet & Batteries: 13.8 | SONNET with Zinc-air: 10.6 Standard: 9.1 Micro: 8.1 RONDO with standard magnet & Zinc-air: 18.5 RONDO with strong magnet & Zinc-air: 21.5 | Weights are in grams. Weights of battery packs include batteries. |
| IP RATING (WATER & DUST RESISTANT) | IP57: Naída with PowerCel batteries. IP68: Naída with AquaCase with AquaMic & PowerCel 110 Mini, 110 & 170 Mini batteries. IP68: Neptune sound processor & AquaMic configuration. | IP44: Nucleus 6 processor with disposable battery module. IP57: Nucleus 6 processor with rechargeable battery module. IP68: Nucleus 6 Aqua+ with Aqua+ coil & rechargeable batteries. IP54: Kanso ¹⁷ | IP54: SONNET using standard or rechargeable battery packs. RONDO: Not specified. IP68: SONNET with WaterWear Accessory using P675 (LR44) size Alkaline or Silver Oxide batteries ¹⁸ IP 68: RONDO using WaterWear Accessory using P675 (LR44) size Alkaline or Silver Oxide batteries | IP rating description. Manufacturer's accessories for water use may not be available in all markets. |
| MICROPHONE PLACEMENT | Naída: T-Mic2 at ear canal entrance, dual omnidirectional on top, single omnidirectional in headpiece. Neptune: Single omnidirectional in headpiece, T-Mic with T-Comm accessory. | Nucleus 6 CP910: Dual omnidirectional on top. Nucleus 6 CP920: Dual omnidirectional on top. Kanso: Dual omnidirectional | SONNET: Dual omnidirectional on top. RONDO: Single omnidirectional. | Microphone placement, whether on the sound processor or on the headpiece or on an auxiliary device (T-Mic at the ear canal) is for better hearing in noise, and for natural telephone & headphone use. |
| INPUT DYNAMIC RANGE (IDR) | Up to 80dB | Up to 45dB ¹⁹ | 75dB | IDR discussion. |
| SOUND CODING STRATEGIES | CIS, MPS, HiRes-P/S, HiRes F120-P/S, ClearVoice, HiRes Optima ²⁰ | ACE, CIS, SPEAK | HD-CIS, FSP, FS4, FS4-p | Sound coding strategies are different ways to "hear" sound, and some may not be approved for pediatric use, but may be available "off-label." |
| PROGRAM SLOTS | Naída: 5 ²¹ Neptune: 3 | Nucleus 6: 4 Kanso: 4 | SONNET: 4 RONDO: 4 | |

¹⁷ A silicone Kanso Aqua+ cover will be available.

18 Pending regulatory approval in some markets; may not be available in all markets. WaterWear Accessory cannot use Zinc-Air batteries.

19 (IIDR) Instantaneous Input Dynamic Range - the IDR at any given moment within a total available range of 75dB.

20 HiRes Optima processing on the HiRes Fidelity 120 platform increases battery life.

21 Up to 10 programs stored in processor memory for bilateral recipients; Intellilink automatically recognizes & selects which implant the processor is fitted on.

| | ADVANCED BIONICS | COCHLEAR | MED-EL | COMMENTS |
|--|--|---|--|--|
| EAS (HYBRID) SOUND PROCESSING | Naída: Yes ²² Neptune: No | Nucleus 6: Yes Kanso: No | SONNET: Yes ²³ RONDO: No | Processor includes hearing aid functionality to use with preserved residual hearing. Information here. Advanced Bionics and MED-EL refer to a combined CI/HA as "Electro-Acoustic Stimulation (EAS)" and Cochlear refers to a combined CI/HA as a "Hybrid." |
| USER CONTROLS | Naída: Button functions for program changing, volume level, microphone sensitivity & standby mode; bilateral recipients can use one MyPilot to adjust both processors. QuickSync feature enables simultaneous volume & program setting adjustments on both sound processors. Neptune: Program switch, volume dial, sensitivity dial | Nucleus 6: Button functions for on/off, program changing, volume level, microphone sensitivity & telecoil on/off; bilateral recipients can use one Remote Assistant or Remote Control to adjust both processors. Kanso: Button functions for on/off, program changing, turning audio sources on/off, other functions available using Remote Assistant or Remote Control. | SONNET: Battery pack lock controls on/off, all other functions available on the FineTuner. Bilateral recipients can use one FineTuner to adjust both processors. RONDO: On/off switch. All functions available on the FineTuner. Bilateral recipients can use one FineTuner to adjust both processors. | User controls are clinician enabled. |
| SOUND PROCESSOR TO IMPLANT REGISTRATION | Naída: Yes ²⁴ Neptune: Yes | Nucleus 6: No Kanso: No | SONNET: No RONDO: No | Capability preventing a sound processor from functioning with an uncomfortable or painful stimulation when use is attempted on a different recipient or contralateral implant for bilateral recipients. |
| ALERTS VISUAL LED | Naída: Yes Neptune: Yes | Nucleus 6: Yes Kanso: Yes | SONNET: Yes RONDO: Yes | Programmable visual status alerts can warn caregivers, such as parents, caregivers or teachers, of functions and/or problems. |
| ALERTS PRIVATE AUDIBLE | Naída: Yes Neptune: Yes | Nucleus 6: Yes Kanso: Yes | SONNET: Yes RONDO: Yes | Programmable audible status alerts can warn the user of functions and/or problems. |
| BATTERY LIFE RECHARGABLE MANUFACTURER CLAIMS OF MAXIMUM OPERATING TIME | Naída PowerCel 110/110 Mini: 17 hours 170/170 Mini: 27 hours 230: 36 hours Neptune Ni-MH AAA: 21 hours | Nucleus 6 Compact: 18 hours Standard: 31 hours Kanso N/A | SONNET Standard: 10 hours Micro: 7 hours RONDO N/A | Programming algorithms trade battery life for hearing performance. For BTE processors each manufacturer may have off the ear battery options. |
| BATTERY LIFE DISPOSABLE MANUFACTURER CLAIMS OF MAXIMUM OPERATING TIME | Naída Zinc-Air: 56 hours AAA: 183 hours Neptune Alkaline AAA: 21 hours Lithium AAA: 30 hours | Nucleus 6 Zinc-air: 60 hours Kanso Zinc-air: 16 hours | SONNET Zinc-air: 60 hours RONDO Zinc-air: 90 hours | Zinc-air batteries (675) are disposable; others are rechargeable. |

Pending regulatory approval.

Pending regulatory approval.

Naída sound processors can load the correct programs for either ear automatically using the Intellilink safety feature.

| | ADVANCED BIONICS | COCHLEAR | MED-EL | COMMENTS |
|------------------------|--|--|--|--|
| GLOBAL WARRANTY | Naída Processor: 3 years UHP, T-Mic & Cables: 3 years Neptune: 3 years UHP, AquaMic & Cables: 3 years Global warranty | Nucleus 6 Processor: 3 years Coil & Cables: 3 years Kanso: Not specified. Global Warranty (not published) | SONNET: (Market variable) 3 years Coil & Cables: 3 years RONDO: (Market variable) 3 years Global Warranty (not published) | Warranty period may start on day of initial activation, varies by country. Manufacturers may offer a one-time replacement for loss or accidental damage during the initial warranty period, depending on market. In USA, when the manufacturer |
| USA\CANADA WARRANTY | Naída processor: 5 years ²⁵ UHP, T-Mic & Cables: 5 years Battery Charger: 5 years Neptune: 5 years UHP, AquaMic & Cables: 5 Years USA Warranty | Nucleus 6 Processor: 5 years ²⁶ Coil & Cables: 5 years Kanso: Not specified. USA Warranty | SONNET: 5 years ²⁷ RONDO: 5 years USA Warranty | warranty expires repair or replacement may be covered by insurance. Always check with your implant clinic & manufacturer for specific warranty information. |
| DIRECT CONNECT | Naída: Yes, with Phonak ComPilot Neptune: Yes | Nucleus 6 CP910: Yes, with audio cable into the accessory socket Nucleus 6 CP920: No Kanso: No | SONNET: Yes, with FM Battery Pack Cover using Euro Audio adapter RONDO: Yes, with Mini Battery Pack using Euro Audio adapter | Audio cable plugged directly into processor or accessory. Bilateral recipients may be able to listen in stereo. |
| AUXILIARY INPUT | Naída: Accessory socket on Phonak ComPilot Neptune: Accessory socket, T-Mic with T-Comm accessory | Nucleus 6 CP910: Accessory socket on Cochlear Wireless Mini Microphone & on Cochlear Wireless Mini Microphone 2+ Nucleus 6 CP920: None Kanso: None | SONNET: Accessory socket on bottom of FM Battery Pack Cover RONDO: Accessory socket on bottom of Mini Battery Pack | Auxiliary input is used to connect to audio sources with wires; wireless capabilities eliminate the need for wires. |
| TELECOIL | Naída: Yes Neptune: Yes, with T-Comm accessory. | Nucleus 6: Yes Kanso: Yes | SONNET: Yes RONDO: Yes | Telecoil provides wireless (magnetic induction) access to hearing aid compatible telephones, and induction loop systems in many public & private buildings or areas. |
| FM | Naída: Yes, with Roger 17 (Phonak) receiver Neptune: Yes, MLxi & Phonak SmartLink+ using Euro FM port | Nucleus 6 CP910: Yes, with Roger 14 (Phonak) receiver Kanso: Not specified. | SONNET: Yes, with FM Battery Pack Cover using Euro Audio adapter RONDO: Yes, with Mini Battery Pack using Euro Audio adapter | FM is a wireless analog or digital transmission from a micro-phone or other transmitter either directly to the processor or gateway device. |
| WIRELESS STREAMING | Naída: Yes, with Phonak ComPilot Neptune: Yes, using direct audio input with a 3 rd party system | Nucleus 6: Yes, with Cochlear Wireless Phone Clip, Cochlear Mini Microphone or Cochlear TV Streamer Kanso: Yes, with Cochlear Wireless Phone Clip, Cochlear Mini Microphone or Cochlear TV Streamer | SONNET: Yes, using telecoil with a 3 rd party system ²⁸ RONDO: Yes, using telecoil with a 3 rd party system | External Bluetooth type adapters can be used on sound processors with direct connect inputs or via FM transmitters. |

USA & Canada only; Naída & Neptune sound processors are 5 years as part of an initial "implant kit" and are 3 years as part of any "upgrade kit;" other parts & accessories are 1 year.

15 or Life" program reported as extended to the Nucleus 6 system, and is "Three (3) year warranty when purchased as part of an upgrade."

17 Reportedly the 2012 five year warranty program extends to the SONNET and RONDO sound processor systems.

28 Additional wireless capability will need to be enabled for future use.

| | ADVANCED BIONICS | COCHLEAR | MED-EL | COMMENTS |
|---|---|---|---|---|
| WIRELESS BILATERAL CONTROLS | Naída: Yes Neptune: No | Nucleus 6: No Kanso: No | SONNET: No RONDO: No | Bilateral recipients can control both processors from either processor. |
| WIRELESS CONTRALATERAL STREAMING | Naída: Yes Neptune: No | Nucleus 6: No Kanso: No | SONNET: No RONDO: No | Sound processor and compatible hearing aid communicate wirelessly for audio streaming, useful for telephone calls and situations where the desired sound is on one side, e.g. in a car. |
| WIRELESS BIMODAL STREAMING | Naida: Yes, with compatible Phonak hearing aid Neptune: No | Nucleus 6: Yes, with compatible Resound hearing aid Kanso: Not specified. | SONNET: Yes, using telecoil RONDO: Yes, using telecoil | Stream sounds from a cochlear implant processor and a compatible hearing aid at the same time. |
| INTEGRATED BIMODAL FUNCTIONALITY | Naida: Yes, with compatible Phonak hearing aid Neptune: No | Nucleus 6: No Kanso: No | SONNET: No RONDO: No | Sound processor and compatible hearing aid communicate wirelessly for audio streaming, sound processing algorithms, unified controls such as program and volume switching. |
| DATA LOGGING | Naída: Yes Neptune: No | Nucleus 6: Yes Kanso: Not specified. | SONNET: Yes RONDO: No | Data logging enables the clinician to review an implant recipient's program use and listening environment to assist in optimizing programming. |
| CLINIC FINDER | Advanced Bionics Clinic Finder | Cochlear Clinic Finder | MED-EL Clinic Finder | Contact clinic to verify that they offer the implant of your choice. |
| MANUFACTURER SPONSORED REHABILITATION | The Listening Room Musical Atmospheres | Rehabilitation resources HOPE (Re)habilitation Resources Listening Tools | Programme for Interactive Listening Activities Bridge to Better Communication Bridge Downloads Soundscape | Rehabilitation is critical for cochlear implant success. Spreadsheet of rehabilitation apps created and maintained by Tina Childress, AuD. |
| MANUFACTURER FORUMS | USA/CAN: Hearing Journey Spain: Hearing Journey Netherlands: Hearing Journey Germany: Hearing Journey France: Hearing Journey | Cochlear Community UK Cochlear Club | Hear Peers | By joining an online forum recipients & implant candidates can learn about cochlear implants from people who use them daily. |

| | ADVANCED BIONICS | COCHLEAR | MED-EL | COMMENTS |
|--|--|--|--|---|
| MANUFACTURER FACEBOOK PRESENCE | English (International) English (UK) Spanish (Latin America & Spain) Dutch (Nederland) German (Germany) French (France) | English (USA & Canada) English (Asia Pacific) English (EU, ME & Africa) | English (USA Coming Soon) English (International) German (Germany) Spanish (Spain) Spanish (Latin America) Italian (Italy) Vietnamese (Viet Nam) | Manufacturer Facebook pages are where manufacturers members share & exchange information. |
| MANUFACTURER SPONSORED SUPPORT | Bionic Ear Association Connect with the Bionic Ear Association (BEA), a support network of volunteers & hearing health professionals. EU Newsletter | Cochlear country website Connect with a global team of volunteers around the world through the Cochlear Awareness Network (CAN). | Connect with the MED-EL US Patient Support Team MED-EL Offices Worldwide | |
| MANUFACTURER SOCIAL MEDIA PRESENCE | YouTube Twitter LinkedIn Pinterest Instagram | YouTube Twitter LinkedIn Pinterest Instagram | YouTube Twitter Blog Google+ | |
| VOLUNTEER PROGRAMS | Bionic Ear Association (BEA): USA, UK, Spain, Germany, Nederlands | Volunteer Advocates (UK) Cochlear Community (US) Cochlear Awareness (AU/NZ) | | Volunteer recipients are often matched with "candidates" who are seeking one-on-one support through in-person contact or by email. |
| RUMORS | "Integrated Speech Processor Headpiece" "Design and Evaluation of a CI Strategy Based on a 'Phantom' Channel" New sound processor for C1 recipients. | | Wireless gateway device for SONNET with an external microphone and 3.5mm connector. | Search the FDA Premarket Approval (PMA) database (MCM code). Manufacturers invest heavily in R&D for better performing implants & smaller sound processors advancing technologies. |

EDITOR'S NOTE: The cochlear implant manufacturers listed in this chart have major global market shares, and are regulatory agency approved in several markets. However, there are other emerging cochlear implant manufacturers in limited markets that can also be considered by an implant candidate depending on county of residence. Listing the other manufacturers in this chart is not practical at this time.